

POWER MEETS PERFORMANCE



PRIMA
5530.S

SPECIFICATIONS LPS 5530.S

Engine

Model	Cummins ISBe 6.7 300HP
Emission Norms	BS-VI
Max. Power	224 kW @ 2200 r/min
Max. Torque	1100 Nm @ 1100-1700 r/min
Engine Capacity	6 692.4 cc
Other Details	Air Filter : Dry Type Remote Mounted; Bore x Stroke: 107 mm x 124 mm
	Fuel Filter : Pre and Fine Filtration with water separator
	After Treatment Unit for Selective Catalytic Reduction (SCR)

Clutch

Clutch	430 mm dia, Dry Friction Type Single Plate, Pull Type
--------	---

Gearbox

Gearbox	TATA G1150 DD Synchromesh Gearbox, 9F + 1R
---------	--

Rear Axle

Rear Axle	TATA RA 114 with Rear Axle Ratio 5.37 RAR
-----------	---

Steering

Steering	470 mm dia, Integral Hydraulic Power Assisted
----------	---

Suspension

Suspension	Parabolic Leaf Spring at Front & Semi-elliptical Multi Leaf Spring at Rear
Shock Absorbers	Hydraulic Double Acting Telescopic Type at Front

Brakes

Brakes	Full Air S-Cam with Automatic Adjuster
Service Brakes	Dual Circuit Full air S-Cam Brakes
Auxilliary	Engine Exhaust Brake - Pneumatically Operated
ABS	Yes, Standard Fitment

Tyres

Size & Type	Front : 295/90R 20 RIB Tubeless Rear : 295/90R 20 LUG Tubeless
-------------	---

Fuel Tank

Fuel Tank	365 + 192 Liters, Plastic
-----------	---------------------------

Chassis Frame

Frame Type	Ladder Type Heavy Duty Frame with Riveted & Bolted Cross Members
Dimensions	285mm x 65mm x 7mm

Cabin

Type	All-new Prima Lx Cabin
Seat	Mechanically suspended & Adjustable Seat for Driver and Twin Accomodation Foldable Bench Seat for Co-Driver
Seat Belts	Emergency Locking Retractor (ELR) Type for Driver and Co-Driver
Side Step for Entry	Three Steps on LH & RH Side with Grab Handles for Easy Entry
Head Lamp	Wrap around Clear Lens Head Lamps 24V, 70 Watt

Optional Fitments	Music System
Air Ventilation Options	A/C Blower

Electrical Systems

Battery	12 V, 100Ah x 2
Alternator	100 A

Dimensions

Wheelbase	3 460 mm
Max. Width	2 585 mm
Overall Length	5 899 mm
Min. Turning Circle dia	13 000 mm

Performance

Max. Gradeability	24% at Crawler
-------------------	----------------

Weights

Kerb Weight	6 890 kg
Max. Permissible FAW	7 000 kg
Max. Permissible RAW	11 500 kg
Max. Permissible GCW	55 000 kg

Warranty - 18 Months or 150,000 km (Which ever comes first) for major aggregates.

ISLAND-WIDE DIMO TATA BRANCH NETWORK

Anuradhapura	0773 087 804	Hambantota	0765 593 632
Polonnaruwa	0773 087 804	Rathnapura	0765 593 632
Batticaloa	0778 152 743	Tissamaharama	0765 593 632
Trincomalee	0778 152 743	Kalutara	0765 593 632
Colombo	0776 565 034	Jaffna	0765 707 291
Galle	0765 593 632	Vavuniya	0765 707 291
Matara	0765 593 632	Mullaitivu	0765 707 291

Kilinochchi	0765 707 291	Kegalle	0765 255 173
Mannar	0765 707 291	Gampaha 1	0777 393 596
Kandy	0768 405 199	Gampaha 2	0773 082 053
Matale	0768 405 199	Monaragala	0773 850 943
Nuwara Eliya	0768 405 199	Ampara	0773 850 943
Badulla	0768 405 199	Puttalam	0771 570 780
Kurunegala	0765 255 173		



©1388

24 Hour Road Side Assistance



Island-wide Tata Genuine Spare Parts Network



Island-wide Service Network



Loyalty Rewards



85+Years of Authority
in Automotive Excellence

THE AUTHORISED DISTRIBUTOR OF TATA VEHICLES

www.dimolanka.com/vehicles/tata
f www.facebook.com/TataMotorsSriLanka

1388